SEFAR PME

The best performing screen printing mesh
SEFAR PME has been specially developed and engineered by Sefar for the needs of high-end industrial screen printing.

Mesh features

SEFAR PME is the best performing range of screen printing mesh for printers who need to expand the capabilities of their screen printing process. The mesh is made from an innovative, high modulus, high tensile strength yarn developed and manufactured by Sefar. This screen printing mesh solution offers stencil makers and printers maximum precision in extremely tight tolerances.
SEFAR PME enables the efficient and reliable production of stencils that allow for printing of the most demanding, high volume products – meeting the highest quality demands.

- High modulus polyester yarn with increased tensile strength
- Balanced and low mesh elongation
- Minimal loss of tension
- Adhesion optimized surface treatment
- Resolution optimized mesh color
- Uncompromised paste and ink release
- Good antistatic properties
- Knot and fault indication

DOWNLOADS

SEFAR PME Leaflet (PDF 223 kb)

SEFAR PME Article list (PDF 645 kb)

SEFAR PME Product data sheet (PDF 344 kb)

Sefar mesh selector app for smartphones

This app supports the screen printing user in selecting the optimal screen printing mesh depending on the application.

Sefar Inc.

111 Calumet Street
Buffalo, NY 14043 – USA

Phone 800 995 0531

sales.us@sefar.com

Go to content

Your Benefits

Screen/stencil maker benefit

- Higher peak tension achievable
- Risk reduction of mesh tearing
- Rapid achievement of stable tension
- Stable mesh geometry during stretching
- Standardized stretching process
- Reduced relaxation time
- Increased productivity
- Homogeneous emulsion application
- Easy, safe capillary film transfer
- High resolution with finest detail adhesion
- Accurate transfer of the printing motif
- UV spectrum matched absorption range
- Adhesive passes easily through the

Printer benefit

- Improved dimensional accuracy
- Risk reduction of stencils tearing on press
- Lowest image distortion
- Dimensionally stable artwork reproduction
- Risk reduction of moiré
- Increased printing speed
- Screen reutilization increases
- Outstanding stencil adhesion expands printable range of fine details
- Increased stencil life time
- Accurate image transfer during printing
- Faithful and less-loss image

Sefar Inc.

111 Calumet Street
Buffalo, NY 14043 – USA

Phone 800 995 0531

sales.us@sefar.com

Go to content

- mesh
- Homogenous adhesive application
- Reduced susceptibility of dust
- Reduction of retouching
- Optimization of mesh utilization
- Cost reduction
- reproduction
- Maintanance of narrowest ink deposit tolerances
- Reduced risk of pinholes
- Error-free printing
- Reduced downtime of the printing press
- Waste and cost reduction

Applications

- Touchscreens
- Keypads / membrane switches
- Printed circuit boards
- Tachometers
- Flat-panel displays
- Solar cells
- Combination stencils
- High-end graphic applications

SEFAR PME has proven unbeatable, especially when going to the limits of what is possible in screen printing, particularly in the industrial production of printed electronic components and functional coatings as well as in all other applications that require highest screen printing performance.

Sefar Inc.

111 Calumet Street
Buffalo, NY 14043 – USA

Phone 800 995 0531

sales.us@sefar.com

Go to content

Whether edge masking or protective coatings using SEFAR PME
(© Danielson Europe BV)

In the fast lane with the highest efficiency and quality printed with SEFAR PME

Clear and durable signs and inscriptions printed with SEFAR PME
(© Danielson Europe BV)

Locations

Sefar BDH Inc.

200 rue Clement Gilbert
Saguenay QC, G7H 5B1 – Canada
Phone: +1 418 690 0888
Fax: +1 418 690 9499

E-Mail

Sefar Inc.

Kansas City, MO – USA
Phone: 800 995 0531
Fax: +1 816 452 2183

E-Mail

Sefar Inc.

Los Angeles, CA – USA
Phone: 800 995 0531
Fax: +1 909 544 5901

E-Mail

Sefar Inc.

Gray, GA – USA
Phone: 800 995 0531
Fax: +1 478 986 6953

E-Mail

Sefar Inc.

111 Calumet Street
Buffalo, NY 14043 – USA
Phone: 800 995 0531
Fax:

E-Mail